



TERRY FAST FIT SERIES

TFF-15-3MP+

Multi-point system with Citryne® scale control

A high-capacity multi-point system that treats water for ice, coffee and fountain beverage from one installation. High-grade carbon reduces taste, odour and corrosion; the built-in Citryne® cartridge eliminates the effects of scale across food-service equipment.

15.9 L/min
TREATED FLOW

0.5 µm
SEDIMENT

8.6 bar
MAX PRESSURE



TFF-15-3MP+ multi-point system

FEATURES

- High-grade activated carbon — reduces taste, chlorine odour & corrosion
- Contains Citryne® — eliminates the effects of scale
- Inhibits hard-water scale
- Reduces costly equipment maintenance
- Full-port shut-off valve
- In-line pressure gauge

CERTIFICATION

- NSF/ANSI 42 — aesthetic effects (Systems IV FF-C15)
- NSF/ANSI 53 — health effects (Systems IV FF-C15)
- NSF/ANSI 169 — scale control (Terry TFF-SC15)

TERRY FAST FIT SERIES

Specification

TFF-15-3MP+ · P/N 57523002

Product dimensions	660 × 483 × 191 mm
Connection	1/2" FNPT
Max. pressure	8.6 bar (125 psi)
Max. temperature	38 °C
Flow rate (untreated)	22.7 L/min
Flow rate (treated)	15.9 L/min
Sediment reduction	0.5 micron
Product weight	7.3 kg

APPLICATIONS

- Ice — cubers ≤ 900 kg, flakers ≤ 1,135 kg
- Coffee — single or multiple brewers
- Fountain beverage — up to 4 carbonators

REPLACEMENT & NOTES

- Includes Citryne® scale-control cartridge
- Replace cartridges every 6 months
- Commercial use only

Specifications are nominal and subject to change without notice. Imperial source data converted to metric.