

ICE &amp; STEAM · TERRY

## FF-CSC15

Twin 15" carbon filters with CITRYNE® scale control for combi ovens and multi-compartment steamers.

7.6 l/min

SERVICE FLOW

8.6 bar

MAX PRESSURE

6 months

CARTRIDGE LIFE



## SPECIFICATION

|                       |                                                                            |
|-----------------------|----------------------------------------------------------------------------|
| Flow rate             | 7.6 l/min (2 GPM)                                                          |
| Filtration            | 0.5 micron with CITRYNE® scale control                                     |
| Application           | Ice makers to 725 kg/day cuber; multi-compartment steamers and combi ovens |
| Scale control         | CITRYNE® food-grade citrate chelation                                      |
| Cartridge life        | up to 6 months                                                             |
| Operating pressure    | 1.7 – 8.6 bar (25 – 125 psi)                                               |
| Operating temperature | 1.7 – 38 °C (35 – 100 °F)                                                  |
| Mounting              | Wall-mounted stainless steel bracket                                       |
| Power supply          | None required — line-pressure operation                                    |
| Certification         | NSF/ANSI 42 — tested and certified                                         |

## REGIONAL WATER CONTEXT · GULF HARD WATER

300–600 mg/L as CaCO<sub>3</sub> **VERY HARD**

30–60 °f · 17–34 °dH · 18–35 gpg

Gulf feed water varies by source: desalinated municipal supply is soft, but groundwater, blended and tank-stored supplies commonly run hard to very hard. Ice, steam and warewash equipment then concentrate that hardness several-fold at the point of use — which is where scale forms fastest.

Specifications are nominal and subject to change without notice. Imperial figures converted from metric source data.