

COLD BEVERAGE · TERRY

TFF-C15-2

Parallel-plumbed twin 15" system — the high-flow beverage and multi-carbonator answer.

15.1 l/min
SERVICE FLOW

8.6 bar
MAX PRESSURE

6 months
CARTRIDGE LIFE



SPECIFICATION

Flow rate	15.1 l/min (4 GPM)
Filtration	1 micron sediment reduction
Connection	3/8" FNPT
Max pressure	8.6 bar (125 psi)
Max temperature	38 °C (100 °F)
Dimensions	546 × 292 × 165 mm (21.5 × 11.5 × 6.5")
Weight	2.7 kg
Certification	NSF/ANSI 42 aesthetic effects; NSF/ANSI 53 health effects
Application	Cubers to 725 kg/day, flakers to 1,130 kg/day; multi-compartment steamers and combi ovens; multiple carbonators
Operating pressure	1.7 – 8.6 bar (25 – 125 psi)
Operating temperature	1.7 – 38 °C (35 – 100 °F)
Mounting	Wall-mounted stainless steel bracket
Power supply	None required — line-pressure operation
Certification	NSF/ANSI 42 — tested and certified

REGIONAL WATER CONTEXT · GULF HARD WATER

300–600 mg/L as CaCO₃ **VERY HARD**

30–60 °f · 17–34 °dH · 18–35 gpg

Gulf feed water varies by source: desalinated municipal supply is soft, but groundwater, blended and tank-stored supplies commonly run hard to very hard. Ice, steam and warewash equipment then concentrate that hardness several-fold at the point of use — which is where scale forms fastest.

